




Higher Precision



Higher Protection Level(IP67)



Higher Speed




Better Price Performance



Moka Robot is a high-tech robot manufacturer providing high quality industrial robots and solutions to our customers. As one of the earliest companies who manufactures industrial robots, we offer professional, timely service and complete robot application solutions. Our robot system is highly stable and mature. After years of development, our products are widely used in industrial automation applications such as welding, painting, handling, palletizing and polishing, both in China and the global market. Our industrial robots are developed by our company with independent intellectual property rights. The motion of each joint of the robot is realized by high performance servo motors and a high precision reducers. The core advantages of our industrial robots include: cost-effective, compact structure, highly reliable, high speed, high precision, easy to operate and easy to maintain. For details, please visit www.mokarobot.com.

Honorary qualifications





MB SERIES

SCARA ROBOTS



MB04SC-300



MB04SC-400



MB10SC-500



MB10SC-600



MB10SC-700



MB10SC-800



MB25SC-800



MB25SC-900



MB25SC-1000

MB SERIES

SMALL 6-AXIS ROBOTS



MB04S-580



MB10S-740



MB10S-920

MB SERIES

GENERAL 6-AXIS ROBOTS



MB20-2100



MB35-1870



MB45-1870



MB SERIES

HEAVY DUTY 6-AXIS ROBOTS



MB180-3200



MB210-2650



MB280-2650

MB SERIES

MR SERIES ROBOTS



MR10C-1488



MR30C-1750



MR10W-1440-D



MR12-2010




MR12Z-1550



MR80E-2250



MR60E-2680

MR10W-1440-D**PAYLOAD : 10KG****REPEATABILITY : $\pm 0.05\text{mm}$** **MOKA****SPECIAL FOR WELDING**


(Gas shielding, Argon arc, Laser, Aluminum, Stainless steel, Carbon steel)

Number of axis	6-axis		Maximum speed	Moving range
Motion radius	1440mm	J1 axis S	285°/s	$\pm 167^\circ$
Power capacity	4.5KVA	J2 axis L	247°/s	+80°~-145°
Max Payload	10KG	J3 axis U	285°/s	+145°~-75°
Protection class	IP56/IP67	J4 axis R	392°/s	$\pm 190^\circ$
Repeatability	$\pm 0.05\text{mm}$	J5 axis B	272°/s	+50°~-210°
Robot mass	210KG	J6 axis T	1353°/s	$\pm 220^\circ$
Built-in air tube	$\Phi 10$	J4 axis R(N.m)		103.5
Input/Output signals	Standard 16 in/16 out 24 VDC	J5 axis B(N.m)		51.84
Mounting position	Floor/frame/ceiling	J6 axis T(N.m)		32.64

MADE BY MOKAROBOT

SPECIFICATIONS

TECHNICAL SPECIFICATION



Installation Environment

Temperature	0-45°C	Humidity	20~80%RH(no condensing)	No corrosive or combustible gas, no water, no splashing	No excessive oil or dust
Vibrations	Below 4.9M/S2 (0.5G)	Altitude	Below 1000M	Away from electromagnetic source	Away from magnetic field

Control cabinet specifications

Overall dimension	700(width)*530(depth)*740(height)mm (with protrusions)
Approximate mass	60KG
Cooling method	Natural cooling
Power specifications	1PH AC220V 50/60HZ
Grounding	Industrial grounding (dedicated grounding, resistance below 100Ω)
Input/Output signal	General signal: 16 input, 16 output
Position control method	Serial communication EtherCAT.TCP/IP
Memory capacity	JOB: 200000 steps, 10000 robot commands (total 200M)
LAN(Host link)	Ethercat(1pc) TCP/IP(1pc)
Control mode	Servo position control
Ambient temperature	In use: 0~ + 45°C, In storage: - 20~ + 60°C
Driver unit	AC servo system (6-axis)
Relative humidity	10%~90%(no condensing)
Vibrate	Below 0.5G

Serial port I/F

RS485(1pc) RS422(1pc) RS232(1pc) CAN(1pc) USB(1pc)

Altitude

Below 1000m. Derate 1% for every additional 100m if over 1000m. Maximum 2000m.

Others

No dust, cutting fluid (including coolant), organic solvent, oil smoke, water, salt, medicine, anti-rust oil, strong microwave, ultraviolet light, X-ray, radiation exposure

Teach pendent specifications

External dimensions	280(width)*220(depth)*120(height)mm (with protrusions)
Gross weight	0.6KG
Material	Reinforced plastics
Display	8 inch color LED, 640*480 pixels
Protection class	IP54
Cable Length	Standard: 6m Optional: 8m/10m/15m

Manipulator

Selector, axis operation, value, mode selection with key (teach mode/auto mode/remote mode), emergency stop, enable, USB port etc



ATTENTION

Please read the user manual and relevant documentations before use.

Contact official staff or distributor of MOKA if there are any errors, faults or if the robot is a harm to human safety.








All data, drawings and specifications provided in this catalog are purely for information purposes and do not constitute a guarantee of these characteristics. The extent of goods delivered and services performed is determined by the subject matter of the specific contract. No liability accepted for errors or omissions.






Robot payload diagram

External dimensions and moving range

P moving range




J4 installation dimensions



End flange installation dimensions

Turning base installation dimensions

Base installation dimensions



MOKA 摩卡

Committed to providing customers with
the most valuable products

WUHU MOKA ROBOT TECHNOLOGY CO., LTD

ADD: NO.19 WEISI ROAD, JIUJIANG DISTRICT, WUHU, ANHUI, CHINA

PHONE: +86-18262626857

WHATSAPP: +86-18262626857

EMAIL: thomas@mokarobot.com

WEBSITE: www.mokarobot.com